




RENTER TILLER

FEATURES



For Renter Tiller specifications and attachments, see back side.

Yard Marvel Mfg. Co., Inc. • 5509 N. Market St. • Spokane, WA 99208 USA
Phone: (509) 487-2428 • Toll-free: (800) 547-9273 (YARD) • Fax: (509) 483-2044
Web: yardmarvel.com • email: info@yardmarvel.com

F A R M A N D G A R D E N
RENTER TILLER
S P E C I F I C A T I O N S

Transmission

14 GA HRS case; flame hardened sprockets
heavy duty roller chains
12 GA HRS reinforcing plates
Needle bearings on hardened race, turning on
Grade 8 bolt
Lubricated with gear oil
Drive shaft and Sprocket one solid piece
precision milled
9 to 1 gear reduction for added power

Wheels

Semi-pneumatic tires 10 x 1.75 with steel
hubs and sealed replaceable ball bearings with
zerk fittings

Frame

1" - 10 GA Heavy wall black iron pipe w/1/8" thick
steel plates

Handlebars

3/4" - 12 GA Black Iron Pipe with reinforcing cross
brace inserted into frame and bolted

Rear Hitch

Patented Back Saver handlebar height adjustment
foot lever can be used from a standing position

Pulleys and Belts

Dual pulley and dual belt system for
increased power to tines
Heavy duty Kevlar reinforced belts

Tines

1/4" x 2-1/4" 5160 alloy spring steel tines bolted to
10 GA plate welded to reinforced precision drawn
steel hubs affixed to rotor pins pressed into shaft.
(Optional)
Bolt-On Hubs available upon request
Wobble Spike Pick Tines available

Safety Features

Full tine hood, protects user from rotating tines
and throwing dirt
Full wrap-around Belt guard
Safety warning decals placed strategically
Finger Tip clutch control for instant start/stop


Tine Shaft

Grade 1045 turned, ground and polished tool steel
hard all the way through (full hard)

Tilling Depth

Maximum depth limited by safety hood to 12"
Reverse tines to surface cultivate to 2" to 4"

Tiller Attachments - Interchangeable systems



Renter Tines

Are heavy duty for
more demanding
commercial use.
25" width only.

Scythe Tines with
divisible hubs allow
for narrow(13-1/2")
or wide (25") as
desired

Trencher Attachments

Carve a trench
2-3/4" wide.
Standard digs
6-1/2" deep.
Deep Dig cuts
8-1/2" deep.

**Straight Cut
Edger** attachment
comes with balance
wheel. Can be
installed on either
side of tiller.

Wedge Cut Edger

Cuts
beveled edge.
Also comes with
balance wheel
and can be
installed on
either side.

**Wobble Spike
Pick Tines** easily
dig into hard or
compacted
surfaces such as
clay. Will work in
rocky ground also.

Sod Stripper

Cuts two lines
2"- 3" deep & 4"
apart. Ideal for
sprinkler systems
or TV cable. Sod
can be rolled up
and re-laid.